



Ensures That You Move Smoothly

vijay Pneumatic Grease Pump are the very latest in mobile lubrication equipment, efficient in operation and easily maneuverable. This is most durable and precise Pneumatic Grease Pump for easy High Pressure Lubrication.

A built-in air regulator controls the input of air to the pump to maintain a constant pump working ratio. This ensures safety and correctly rated grease pressure irrespective of the air supply in the pipeline.

Special Features:-

- ⇒ Single Cylinder
- ⇒ Drum Reservoir Wheel Mounted
- ⇒ Pneumatically Operated



Pneumatic Grease Pump

Standard Accessories:-

- ⇒ Swivel Assembly at Both Ends Of The Hose
- ⇒ Mobile Drum With Cover Locking Assembly
- ⇒ 'Z' Swivel Assembly
- ⇒ Trigger Gun Assembly
- ⇒ Follower Plate Assy.
- ⇒ Spare Repair Kit
- ⇒ Spare Adaptor Kit

Specification: -

Model No	VH -10/15/25/50
Drum Capacity (Kg.)	10/15/25/50 Kg.
Pressure Ratio	50:1
Air Requirement (FAD)	325 LPM
Working Pressure Range	4.5-10.5Kg/Sq.Cm.
Recommended Working Pressure	8.5 Kg/Sq.Cm.
Output at 8.5 Kg/Sq.Cm.	300-400 Gram /Minute
Gun	Trigger Type
Grade Of Grease to be used	Upto Grade NLGI 2
Delivery Hose Length	2.2 Mtrs.
Type Of Hose	High Pressure Wire Braided Hose
ID Of Hose	1/4"



38, Bibijan Street, 1st Floor, Office No.20, (Off Nagdevi Street) Mum-3.
 Tel No- 23447152, 23439556 Fax- 23420498 Email: vijayeng1@hotmail.com
www.vijaylube.com